



GENERAL NOTES FOR TOWN RURAL ROADS:

1. SAND CUSHION LAYER, GRAVEL SUBBASE, AND CRUSHED GRAVEL SURFACE COARSE SHOULD BE CONSTRUCTED TO THE DIMENSIONS SHOWN IN ACCORDANCE WITH CURRENT VTRANS STANDARD SPECIFICATIONS FOR CONSTRUCTION.
2. ALL EXPOSED/DISTURBED EARTH SHALL BE SEEDED AND MULCHED.
3. DITCHES WILL RECEIVE THE FOLLOWING TREATMENTS BASED ON THEIR SLOPES:
 - 0 - 1% SEED AND MULCH
 - 1 - 3% EROSION CONTROL MATTING AND SEED
 - 3%-10% TYPE I STONE FILL WITH MIN. 1.0' DEPTH
4. HORIZONTAL CURVATURE: MINIMUM RADIUS OF CURVATURE FOR NORMAL CROWN OR SUPERELEVATED (BANKED) CURVES SHALL BE PROVIDED PER "A POLICY ON GEOMETRIC DESIGN OF HIGHWAYS AND STREETS" BY AASHTO.



Appendix 1:
Town of Morrystown Road Policy

Rural Road Typical Cross Section

Effective: Nov. 1 2015

DWG.#: 1

SCALE: 1"= 5'

DRN.:SJD

CHK.:TT